



ITEM	Hoshizaki Crescent Ice Maker (Self-Contained Type)
MODEL	KM-30A
AC SUPPLY VOLTAGE	1 Phase 220 - 240V 50Hz
AMPERAGE	1.5A(AT. 32°C, WT. 21°C)
STARTING AMPERAGE	10.0A
ELECTRICAL CONSUMPTION	195W(AT. 32°C, WT. 21°C)
POWER FACTOR	54%
POWER SUPPLY CAPACITY	Min. 0.65kVA(2.73A)
ICE PRODUCTION PER	Approx. 36kg/d(AT. 10°C, WT. 10°C) Approx. 32kg/d(AT. 21°C, WT. 15°C) Approx. 25kg/d(AT. 32°C, WT. 21°C)
WATER CONSUMPTION PER	Approx. 0.142m <sup>3</sup> /d(AT. 10°C, WT. 10°C) Approx. 0.060m <sup>3</sup> /d(AT. 21°C, WT. 15°C) Approx. 0.042m <sup>3</sup> /d(AT. 32°C, WT. 21°C)
SHAPE OF ICE	Crescent Cube
FREEZE CYCLE TIME	Approx. 30Min(AT. 21°C, WT. 15°C)
ICE PRODUCTION PER CYCLE	Approx. 0.71kg / 80pcs(AT. 21°C, WT. 15°C)
MAX STORAGE CAPACITY	Approx. 16kg(Bin Cont Setting Approx. 14kg)
OUTSIDE DIMENSIONS	450mm(W)×610mm(D)×842mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Rear)
INSULATION	Polyurethane Foam
CONNECTIONS-ELECTRIC	Y-type Con.
CONNECTIONS-WATER SUPPLY	Inlet G3/4"(connected at rear side)
CONNECTIONS-DRAIN	Outlet ø25(connected at rear side)
ICE MAKING SYSTEM	Vertical Evaporator with water flow on both sides
HARVESTING SYSTEM	Water Supply Harvest Cycle and Hot Gas Defrost
COMPRESSOR	Hermetic 125W Model QA51K13GAW5-HOLE
CONDENSER	Air-cooled, Fin and Tube type
HEAT REJECTION	460W(394kcal/h)(AT.32°C, WT.21°C)
EVAPORATOR	Vertical type, Stainless Steel and Copper
REFRIGERANT CONTROL	Capillary Tube
REFRIGERANT CHARGE	R134a / 200g
ICE MAKING CONTROL SYSTEM	Float Switch
HARVESTING CONTROL SYSTEM	Hot Gas and Water, Thermistor and Timer
ICE MAKING WATER CONTROL SYSTEM	Timer Controlled, Overflow Pipe
BIN CONTROL SYSTEM	Mechanical Level Switch with Delay
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse
COMPRESSOR PROTECTION	Auto-reset Overload Protector
ICE MAKER PROTECTION	Interlock by Controller Board
WEIGHT	Net weight 39kg / Gross weight 49kg
PACKAGE	Carton 535mm(W)×705mm(D)×955mm(H)
ACCESSORIES	Instruction Manual, Scoop, Adjustable Bolt, Outlet Hose
OPERATION CONDITION	Voltage Range: 198-254V, Ambient Temp: 1-40°C Water Supply Temp.: 5-35°C Water Supply Temp.: 0.7-8bar (0.07-0.8Mpa)

Based on Specs. No. SS-03536

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
2. The ice production depends on the ambient and water temperatures.  
Refer to the instruction manual.

# HOSHIZAKI CRESCENT ICE MAKER(SELF-CONTAINED TYPE) KM-30A

APPROVED OGATA	CHECKED YOSHIDA	DESIGNED YOSHIDA	DRAWN MINEZAWA	SCALE 1/10	TRIGONOMETRY
*	*	△	****	DATE 2008.10.21	DRAWING NO. D03921
APPROVED	DESIGNED	SYMBOL	DATE		SYMBOL △