



ITEM	Hoshizaki Crescent Ice Maker (Self-Contained Type)
MODEL	KM-75A
AC SUPPLY VOLTAGE	1 Phase 220 - 240V 50Hz
AMPERAGE	3.0A(AT. 32°C, WT. 21°C)
STARTING AMPERAGE	13.3A
ELECTRICAL CONSUMPTION	412W(AT. 32°C, WT. 21°C)
POWER FACTOR	57%
POWER SUPPLY CAPACITY	Min. 0.87kVA(3.63A)
ICE PRODUCTION PER	Approx. 72kg/d(AT. 10°C, WT. 10°C) Approx. 70kg/d(AT. 21°C, WT. 15°C) Approx. 55kg/d(AT. 32°C, WT. 21°C)
WATER CONSUMPTION PER	Approx. 0.287m³/d(AT. 10°C, WT. 10°C) Approx. 0.118m³/d(AT. 21°C, WT. 15°C) Approx. 0.071m³/d(AT. 32°C, WT. 21°C)
SHAPE OF ICE	Crescent Cube
FREEZE CYCLE TIME	Approx. 24Min(AT. 21°C, WT. 15°C)
ICE PRODUCTION PER CYCLE	Approx. 1.25kg / 130pcs(AT. 21°C, WT. 15°C)
MAX STORAGE CAPACITY	Approx. 40kg(Bin Cont Setting Approx. 34kg)
OUTSIDE DIMENSIONS	603mm(W)×712mm(D)×842mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Rear)
INSULATION	Polyurethane Foam
CONNECTIONS-ELECTRIC	Y-type Con.
CONNECTIONS-WATER SUPPLY	Inlet G3/4"(connected at rear side)
CONNECTIONS-DRAIN	Outlet φ25(connected at rear side)
ICE MAKING SYSTEM	Vertical Evaporator with water flow on both sides
HARVESTING SYSTEM	Water Supply Harvest Cycle and Hot Gas Defrost
COMPRESSOR	Hermetic 300W Model QA125K26CAW5-HOLE
CONDENSER	Air-cooled, Fin and Tube type
HEAT REJECTION	1050W(904kcal/h)(AT.32°C, WT.21°C)
EVAPORATOR	Vertical type, Stainless Steel and Copper
REFRIGERANT CONTROL	Capillary Tube
REFRIGERANT CHARGE	R134a / 240g
ICE MAKING CONTROL SYSTEM	Float Switch
HARVESTING CONTROL SYSTEM	Hot Gas and Water, Thermistor and Timer
ICE MAKING WATER CONTROL SYSTEM	Timer Controlled, Overflow Pipe
BIN CONTROL SYSTEM	Mechanical Level Switch with Delay
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse
COMPRESSOR PROTECTION	Auto-reset Overload Protector
ICE MAKER PROTECTION	Interlock by Controller Board
WEIGHT	Net weight 51kg / Gross weight 64kg
PACKAGE	Carton 690mm(W)×805mm(D)×955mm(H)
ACCESSORIES	Instruction Manual, Scoop, Adjustable Bolt, Outlet Hose
OPERATION CONDITION	Voltage Range: 198-254V, Ambient Temp: 1-40°C Water Supply Temp.: 5-35°C Water Supply Temp.: 0.7-8bar (0.07-0.8Mpa)

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.

# HOSHIZAKI CRESCENT ICE MAKER(SELF-CONTAINED TYPE) KM-75A

DESIGNED	DRAWN	SCALE	TRIGONOMETRY
****	DATE	1/10	
DATE	2008.10.23	DRAWING NO.	SYMBOL
		D03926	△